

# Evaluation of infrasound avalanche detection systems

Stephanie Mayer, Alec van Herwijnen, Giacomo Ulivieri and Jürg Schweizer



#### **Motivation**












## An avalanche rarely comes alone







# Can you see an avalanche?

09.03.2017, view from ski area Bellwald






Can you see an avalanche?

Should I close the road?!











# Avalanche activity data is needed to forecast avalanche danger





# Avalanche activity data is needed to forecast avalanche danger






# Can infrasound detection systems reliably detect avalanches?

Swiss Federal Office of the Environment (FOEN)




## Avalanches produce soundwaves








## Detection systems record infrasound








#### Direction of avalanche is identified





## Evaluation of the detection system



## **Visual monitoring**





→ In total 840 observed avalanches





#### Infrasound vs. visual observation

110 infrasound alarms

VS.

840 observed avalanches






- infrasound system
- infrasound alarm
- avalanches 2015/16
- avalanches 2016/17








## **Probability of detection**







## **Probability of detection**




Width: 300 m Length: 2.5 km Distance: ~2 km







## Influence of topography



#### Conclusion

Can infrasound detection systems reliably detect avalanches?

- > small avalanches (< 100 x 100 m<sup>2</sup>)
- large avalanches (~100 x 1000 m²) within a distance < 3 km</p>



topographic barriers have a strong influence

#### Conclusion

Can infrasound detection systems reliably detect avalanches?

- > small avalanches (< 100 x 100 m<sup>2</sup>)



- topographic barriers have a strong influence
  - Important additional information for local avalanche safety services






## Thank you for your attention!





## Infrasound array








## **Detection algorithm**

- 1. Amplitude threshold → reduce amount of data
- 2. Discriminate from other infrasonic sources, three criteria:
  - a) Decrease in angle of height
  - b) Azimuth rotation
  - c) Minimal signal duration.




#### What is infrasound detection?

Infrasound = sound of frequency < 16 Hz</li>



#### Characteristic of detection



False alarm rate: 10-28%